


“Environment-friendly” Fine-blaking oils

1. Features

Our FB-2** series are “Environment-friendly” Fine-blanking oils composed of more than 80% of biodegradable raw materials.

Four different types of viscosity are available to suit the application, such as for light-duty/heavy-duty operation or thickness of ferrous material upto 6.0mm.

2. Physical property and ingredients

		FB-203	FB-205	FB-207	FB-209	Application (Example)
Appearance	Visual	Amber clear liquid				
Kinematic Viscosity	(40°C)mm ² /s	70	104	156	216	
Four ball test (200rpm)	Kgf/cm ³	15.0<				
Copper corrosion test	100 deg C 1 hour	4a				
Ingredients	Oiliness Agent、 Antioxidants、 Friction modifier					

3. Handling and Storage

- Keep container closed and store in a cool, well-ventilated place. DO NOT handle or store near an open flame, heat or other sources of ignition.
- Please refer to the Safety Data Sheet for further information.
- The shelf life under un-opened condition is twelve months.
- Regulatory information
 Fire Service Act: Category IV, Class III petroleum.
 Industrial Safety and Health Act: The products DO NOT contain any chemical substances listed.
 Pollutant Release and Transfer Register Law: Same above.
 Ordinance on Prevention of Hazards Due to Specified Chemical Substances: Same above.
 Ordinance on Prevention of Organic Solvent Poisoning: Same above.
- The products are available in 18-liter can and 200-liter drum.

For further information, please contact
 NIHON KOHSAKUYU CO., LTD. – Tokyo Office
 5-29-14 Shiba, Minato-ku, Tokyo, 108-0014 JAPAN
 Tel: (+81) 03-3455-5511 / Fax: (+81) 03-3453-2667
 E-mail: sales@nihon-kohsakuyu.co.jp
 URL: www.nihon-kohsakuyu.co.jp